

CONTENTS

LIST OF PRINCIPAL SYMBOLS AND ABBREVIATIONS	9
1. INTRODUCTION	13
Bibliography	16
2. SOLID PHASE SAMPLING ACCURACY FROM GAS FLOWING IN A CONDUIT USING AN ENTRY NOZZLE	19
2.1. Object of the research and the background of the problem	19
2.2. Sampling accuracy of homogeneous dust particles for the tested entry nozzle – aspiration characteristics	25
2.3. Sampling error of polydisperse particulate matter	43
2.4. Summary and conclusion	45
Bibliography	46
3. APPROXIMATIVENESS OF THE DETERMINED FLUE GAS MEAN DUST CONCENTRATION IN A CONDUIT DUE TO SAMPLING GAS HAVING A SPATIAL DUST CONCENTRATION DISTRIBUTION	49
3.1. Spatial representativeness of a taken dust-laden sample	49
3.2. Data on the flows of dust-laden gases and the sampling of them in installations	53
3.3. Simulation calculation assumptions	55
3.4. Simulation base distributions	57
3.5. Evaluation of the adopted simplification in simulation distributions	61
3.6. Error of the determined total dust concentration in the simulated cases	62
3.7. Uncertainty of the determined total dust concentration	67
3.8. Discussion and application of the results. Summary	70
Bibliography	73
4. ACCURACY OF SAMPLING PARTICULATE MATTER OF UNIDENTIFIED PROPERTIES FROM INDUSTRIAL DUST REMOVAL PLANTS	76
4.1. The problem's essence and the concept of quantitative approach to it	76
4.2. Particle size distributions of the simulated dusts	77
4.3. Calculation of potential sampling error	81
4.4. Analysis of the sampling error results and summary	83
Bibliography	95

5. SUPPLEMENT TO THE COMPREHENSIVE APPROACH TO THE GRAVIMETRIC MEASUREMENT OF FLUE GAS DUST CONCENTRATION	98
Bibliography	104
6. PRECISION OF THE SELECTION OF THE SIZE OF A DUST COLLECTOR OF A KNOWN GRADE EFFICIENCY CHARACTERISTICS IN THE ASPECT OF THE WAY OF DESCRIBING THE PARTICLE SIZE DISTRIBUTION AT THE DISCHARGE FROM INDUSTRIAL PROCESS (CASE OF A CYCLONE)	106
6.1. Problem presentation and the scheme of calculation work	106
6.2. Initial data and the general assumptions of the calculations	112
6.2.1. Gas and dust removal parameters	112
6.2.2. Test dusts, theoretical cut-off diameter	112
6.2.3. Dust removal grade efficiency	113
6.3. Sizing of the cyclones	114
6.4. Calculation of the total dust removal efficiency of the cyclones	116
6.5. Discussion of the results. Conclusions and summary	118
Bibliography	120
7. ERROR OF THE DETERMINATION OF THE RESPIRABLE DUST AMOUNT IN WORKPLACE AIR RESULTING FROM THE SHAPE OF THE PRE-SELECTOR CHARACTERISTICS	122
7.1. Problem description and solving method	122
7.2. Simulation characteristics of the pre-selectors and dusts. The sequence of the calculations	126
7.3. Calculated mass error of respirable dust. Conclusions and summary	128
Bibliography	131
8. ESTIMATION OF THE VARIANT USAGE OF THE DRAG COEFFICIENT EQUATIONS IN THE CALCULATION OF STANDARD SETTLING VELOCITY OF A DUST PARTICLE. THE EXPLICIT FORMULA FOR CALCULATING THE VELOCITY	133
8.1. Role of the drag coefficient in calculating settling velocity. The concept of the carried out calculations	133
8.2. Notations for the determination of the drag coefficient adopted to the comparative calculations	138
8.3. Differences in the calculated u_p values	140
8.4. Explicit relationship for the calculation of standard settling velocity, its accuracy and application. Summary	152
Bibliography	157
9. SUMMARY	160
Appendix A. Way of determining the gas radial velocity field based on the axial velocity field near the entry nozzle inlet opening	164
Appendix B. Way of determining the component velocities of a solid particle in the identified gas velocity field near the entry nozzle inlet opening ...	166

Appendix C. Test calculation of the reduction of gas volumetric flow rate with omitting the laminar sub-layer	169
Appendix D. Analytical descriptions of the cumulative particle size distributions of the adopted test dusts	171
Appendix E. Details of the calculation of the cyclones for the six test dusts	173
Abstract	177